



REVISED 11-2013

Security Solutions

Product Line-up



SAMSUNG TECHWIN

SAMSUNG



NEW SNF-7010/7010V  3MP Full HD 360° Fisheye • 1080p resolution w/ dewarped images • 360° fisheye view • Wide Dynamic Range • Variety of viewing compositions: panorama, quad, user selectable region • Analytics, bi-directional audio • IK10, IP66 (SNV-7010V)	SNB-7002  3MP Full HD 1080p • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Audio/Face/Motion Detection • Simple focus	SNB-7001  3MP Full HD 1080p • 1080p resolution @ 30fps • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Tamper detection	SNO-7082R  3MP Full HD 1080p Weatherproof IR • 2.8x motorized lens (3~8.5mm) • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Audio/Face/Motion Detection • SD memory (4GB included)	SND-7082/7082F  3MP Full HD 1080p Dome • 2.8x motorized lens (3~8.5mm) • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Audio/Face/Motion Detection
NEW SND-7061/7011  3MP Full HD 1080p • SND-7061: 2.8x (3~8.5mm) varifocal lens; • SND-7011: 3mm fixed lens • 1080p resolution @ 30fps • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Tamper detection	SNV-7082  3MP Full HD 1080p Vandal • 2.8x motorized lens (3~8.5mm) • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Flush Mount • IP66, IK10	SNV-7080R  3MP Full HD 1080p IR Vandal • 2.8x motorized lens (3~8.5mm) • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Flush Mount • IP66, IK10	SNB-6004  2MP Full HD 1080p • 1080p resolution @ 60fps • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • P-Iris, Simple focus	SNO-6084R  2MP Full HD 1080p IR • 1080p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • Simple focus, IP66, IK10
NEW SNO-6011R  2 MP Full HD 1080p IR • 1080p resolution @ 30fps • 3.8mm fixed lens • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • IP66	SND-6084R  2 MP Full HD 1080p IR • 1080p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus	SND-6084  2 MP Full HD 1080p • 1080p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus	NEW SND-6011R  2 MP Full HD 1080p IR • 3.8mm fixed lens • 1080p resolution @ 30fps • Wide Dynamic Range • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics	NEW SNV-6012M  2MP Full HD 1080p Vandal Mobile • 1080p resolution @ 60fps • 3mm fixed lens (103.1° view) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • IP66/IK10, M12 connector, EN50155, EN50121
NEW SNV-6084  2 MP Full HD 1080p Vandal • 1080p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • Simple focus, IK10, IP66	SNV-6084R  2 MP Full HD 1080p IR Vandal • 1080p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • Simple focus, IK10, IP66	NEW SNP-6200RH  2MP Full HD 1080p 20x IR PTZ • 1080p resolution @ 30fps • 20x optical zoom • IR distance 100m (328ft) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, IK10, IP66	NEW SNP-6201/6201H  2 MP Full HD 1080p 20x PTZ • 1080p resolution @ 30fps • 20x optical zoom • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, IK10 & IP66 (SNP-6201H) • Heater by PoE+ (SNP-6201H)	SNP-6200/6200H  2 MP Full HD 1080p 20x PTZ • 1080p resolution @ 30fps • 20x optical zoom • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, IK10 & IP66 (SNP-6200H)
NEW SNB-5004  1.3 MP HD 720p • 720p resolution @ 60fps • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics • P-Iris, Simple focus	SNB-5000  1.3 MP HD 720p • 720p resolution @ 30fps • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics	SNB-5001  1.3 MP HD 720p • 720p resolution @ 30fps • Multiple streaming simultaneously • Tamper detection	SNZ-5200  1.3 MP HD 720p 20x Zoom • 720p resolution @ 30fps • 20x optical zoom • Multiple streaming simultaneously • Analytics	SNO-5080R  1.3 MP HD 720p IR • 720p resolution @ 30fps • 3.6x (2.8~10mm) varifocal lens • Multiple streaming simultaneously • Analytics • IP66

NETWORK

SAMSUNG

SAMSUNG TECHWIN

NEW SND-5084  1.3MP HD 720p • 720p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus	SND-5080/5080F  1.3MP HD 720p • 720p resolution @ 30fps • 3.6x (2.8~10mm) varifocal lens • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus	SND-5061/5011  1.3 MP HD 720p Dome • 720p resolution @ 30fps • SND-5061: 2.8x (3~8.5mm) varifocal lens; • SND-5011: 3mm fixed lens • Multiple streaming simultaneously • Tamper detection	SND-5010  1.3 MP HD 720p • 720p resolution @ 30fps • 3mm fixed lens • Multiple streaming simultaneously • Tamper detection	NEW SNV-5084  IP66 IK10 1.3MP HD 720p Vandal • 720p resolution @ 60fps • 2.8x motorized lens (3~8.5mm) • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus, IK10, IP66
SNV-5080  IP66 IK10 1.3 MP HD 720p Vandal • 720p resolution @ 30fps • 2.8x motorized lens (3~8.5mm) • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus • IK10, IP66	SNV-5080R  IP66 IK10 1.3 MP HD 720p IR Vandal • 720p resolution @ 30fps • 2.8x motorized lens (3~8.5mm) • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, Simple focus • IK10, IP66	SNV-5010  IP66 IK10 1.3 MP HD 720p Vandal • 720p resolution @ 30fps • 3mm fixed lens • Multiple streaming simultaneously • Tamper detection • IK10, IP66	SNP-5300/5300H  IP66 1.3 MP HD 720p 30x PTZ • 720p resolution @ 30fps • 30x optical zoom • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, IP66 (SNP-5300H)	SNP-5200/5200H  IP66 IK10 1.3 MP HD 720p 20x PTZ • 720p resolution @ 30fps • 20x optical zoom • Wide Dynamic Range • Enhanced Digital Image Stabilization • Smart compression (Region of Interest Encoding) • Multiple streaming simultaneously • Analytics, IK10 & IP66 (SNP-5200H)
SNB-3002  4CIF • 4CIF resolution @ 30fps • Wide Dynamic Range • Multiple streaming simultaneously • Tamper detection	SND-3082/3082F  4CIF • 4CIF resolution @ 30fps • 3.9x varifocal lens (2.8~11mm) • Wide Dynamic Range • Multiple streaming simultaneously • Tamper detection • Flush mount	SNV-3120  IP66 IK10 4CIF 12x Vandal • 4CIF resolution @ 30fps • 12x optical zoom • Wide Dynamic Range • Multiple streaming simultaneously • Analytics • IK10, IP66	SNV-3082  IP66 IK10 4CIF Vandal • 4CIF resolution @ 30fps • 3.9x (2.8~11mm) varifocal lens • Wide Dynamic Range • Multiple streaming simultaneously • Tamper detection • IK10, IP66	SNP-3371TH/3371H/3371  IP66 IK10 4CIF 37x PTZ • 4CIF resolution @ 30fps • 37x optical zoom • Wide Dynamic Range • Multiple streaming simultaneously • Analytics • Auto tracking (SNP-3371H) • IK10 & IP66 (SNP-3371TH/3371H)
SNP-3302H/3302  IP66 IK10 4CIF 30x PTZ • 4CIF resolution @ 30fps • 30x optical zoom • Wide Dynamic Range • Multiple streaming simultaneously • Analytics • IK10 & IP66 (SNP-3302H)	SNP-3120/3120VH  IP66 4CIF 12x PTZ • 4CIF resolution @ 30fps • 12x optical zoom • Wide Dynamic Range • Multiple streaming simultaneously • Analytics • IP66 (SNP-3120VH)	SNB-1001  VGA • VGA resolution @ 30fps • Multiple streaming simultaneously • Face detection	SNO-1080R  IP66 VGA Weatherproof IR • VGA resolution @ 30fps • 3.5x (2.2~7.7mm) varifocal lens • Multiple streaming simultaneously • Face detection • IP66	SND-1080/1011  VGA • VGA resolution @ 30fps • SND-1080: 3.5x (2.2~7.7mm) varifocal lens; SND-1011: 3mm fixed lens • Multiple streaming simultaneously • Face detection
SNV-1080  IP66 IK10 VGA Vandal • VGA resolution @ 30fps • 3.5x (2.2~7.7mm) varifocal lens • Multiple streaming simultaneously • Face detection • IK10, IP66	SNV-1080R  IP66 IK10 VGA Vandal IR • VGA resolution @ 30fps • 3.5x (2.2~7.7mm) varifocal lens • Multiple streaming simultaneously • Face detection • IK10, IP66	SRN-1000  Network Video Recorder • 64 Channel • 100Mbps recording bit rate • Max 5MP resolution support • Max. 8 internal HDD • 2 external ports, supports expansion bay • RAID 5 support • Smart recording and search	SRN-1670D/470D  Network Video Recorder • Max.16 Channel/4 Channel • 64Mbps recording bit rate • Max. 5 internal HDD (SRD-1670D), Max. 1 internal HDD (SRD-470D) • 2 external ports, supports expansion bay • Full HD 1080p resolution support • Local monitor output : HDMI & VGA • DVD/USB backup support	SPE-400B/1600R  4CH Blades /16CH Video Encoder Rack • 4CIF resolution @ 30fps • Multiple streaming simultaneously • 10/100/1000BASE-T • SPE-1600R : extension rack • 4 slots for SPE-400B

ANALOG

SAMSUNG

SAMSUNG TECHWIN

SCB-4000  700TV Lines • 600TVL (Color), 700TVL (B/W) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • Analytics • RS-485	NEW SCB-3003  700TV Lines • 960H • 700TVL (Color & B/W) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • Wide Dynamic Range • Analytics • Coaxial : Pelco-C (Coaxitron)	SCB-3001  650TV Lines • 650TVL (Color), 700TVL (B/W) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485	SCB-3000  600TV Lines • 600TVL (Color), 700TVL (B/W) • Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W) • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485	SCB-2004  700TV Lines • 700TVL (Color), 650TVL (B/W) • Min. 0.1Lux @ F1.2 (Color) • Analytics • Coaxial : Pelco-C (Coaxitron)
SCB-2002  650TV Lines • 650TVL (Color), 700TVL (B/W) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • Analytics • Pelco-C (Coaxitron), RS-485	NEW SCB-2005  700TV Lines • 960H • 700TVL (color & B/W) • Min. 0.1Lux @ F1.2 (Color) • Motion detection • Coaxial : Pelco-C (Coaxitron)	SCB-2001  600TV Lines • 600TVL (Color), 700TVL (B/W) • Min. 0.05Lux @ F1.2 (Color), 0.01Lux (B/W) • Analytics • RS-485	SCB-2000  600TV Lines • 600TV L (Color) • Min. 0.05Lux @ F1.2 (Color) • Coaxial : Pelco-C (Coaxitron)	SCB-3020  600TV Lines ATM • 600TVL (Color) • Min. 0.45Lux @ F2.0 (Color) • 3.7mm fixed lens • Wide Dynamic Range • Analytics
SCZ-3430  600TV Lines, 43x Zoom • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W) • 43x (3.2 ~ 138.5mm) • Wide Dynamic Range • Analytics	SCZ-3370/2370  600TV Lines, 37x Zoom • 600TVL (Color), 700TVL (B/W) • SCZ-3370: 0.7Lux @ F1.6 (Color), 0.07Lux (B/W) ; SCZ-2370: 0.2Lux @ F1.6 (Color), 0.02Lux (B/W) : • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485	NEW SCZ-2373/2273  680TV Lines, 37x/27x Zoom • 680TVL (Color) • Min. 0.2Lux @ F1.6 (Color), 0.01Lux (B/W) • SCZ-2373: 37x; SCZ-2273: 27x • Pelco-C (Coaxitron), RS-485	SCZ-2250  600TV Lines, 25x Zoom • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.65 (Color), 0.02Lux (B/W) • Analytics	SCO-2080  IP66 600TV Lines • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.6x (2.8 ~ 10mm) varifocal lens • Pelco-C (Coaxitron), RS-485 • IP66
SCO-3080R  IP66 650TV Lines, IR • 650TVL (Color), 700TVL (B/W) • 3.6x (2.8 ~ 10mm) varifocal lens • IR distance 50m (164ft) • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485 • IP66	SCO-2081R  IP66 700TV Lines, IR • 700TVL (Color) • 3.6x (2.8 ~ 10mm) Varifocal lens • IR distance 50m (164ft) • Analytics • Coax : Pelco-C (Coaxitron), RS-485 • IP66	NEW SCO-2040R  IP66 650TV Lines, Compact IR • 650TVL (Color) • 8mm fixed lens • IR distance 25m (82ft) • IP66	SCO-2120R  IP66 600TV Lines, 12x Zoom, IR • 600TVL (Color), 700TVL (B/W) • IR distance 70m (230ft) • Analytics • Coaxial : Pelco-C (Coaxitron), RS-485 • IP66	SCO-2080R/2080RH  IP66 600TV Lines, IR • 600TVL (Color), 700TVL (B/W) • IR distance 50m (164ft) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion detection • Coaxial : Pelco-C (Coaxitron), RS-485 • IP66
SCO-1020R  IP66 520TV Lines, Compact IR • 520TVL (Color) • IR distance 15m (48ft) • 3.6mm fixed lens • IP66	NEW SCD-3083  700TV Lines • 960H • 700TVL (Color) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • 3.6x motorized lens (2.8 ~ 10mm) • Wide Dynamic Range • Analytics • Coaxial : Pelco-C (Coaxitron)	SCD-3081/2081  650TV Lines • 650TVL (Color), 700TVL (B/W) • Min. 0.1Lux @ F1.2 (Color), 0.01Lux (B/W) • 3.9x (2.8 ~ 11mm) varifocal lens • Wide Dynamic Range (SCD-3081) • Analytics (SCD-3081), Motion detection (SCD-2081) • Coax : Pelco-C (Coaxitron)	SCD-3080/2080  600TV Lines • 600TVL (Color), 700TVL (B/W) • SCD-3080: Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W); SCD-2080: 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.9x (2.8 ~ 11mm) / 3.6x (2.8 ~ 10mm) varifocal lens • Wide Dynamic Range (SCD-3080) • Coax : Pelco-C (Coaxitron) • Wide Dynamic Range	SCD-2080E/2060E  600TV Lines • 600TVL (Color), 700TVL (B/W) • SCD-2080E: Min. 0.15Lux @ F1.2 (Color) • SCD-2080E: 3.6x (2.8 ~ 10mm) varifocal lens; • SCD-2060E: 2.4x (2.5 ~ 6mm) varifocal lens; • Motion detection • Coaxial : Pelco-C (Coaxitron)

877-213-1222 • www.samsung-security.com

ANALOG

SAMSUNG

SAMSUNG TECHWIN

SCD-2082/2022  700TV Lines • 700TVL (Color), 650TVL (B/W) • Min. 0.1Lux @ F1.2 (Color) • SCD-2082: 3.6x (2.8 ~ 10mm) varifocal lens; • SCD-2022: 3.8mm fixed lens • Motion detection • Coaxial : Pelco-C (Coaxitron)	SCD-2020/2040  600TV Lines • 600TVL (Color) • Min. 0.15Lux @ F1.2 • SCD-2020: 3.7mm fixed lens; • SCD-2040: 8mm fixed lens • Coaxial : Pelco-C (Coaxitron)	SCD-2010  600TV Lines • 600TV lines • Min. 0.04Lux @ F1.2 • 3mm fixed lens • Coaxial : Pelco-C (Coaxitron)	SCD-2080  600TV Lines • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion detection • Coaxial : Pelco-C (Coaxitron)	SCD-1020/1040/1080  600TV Lines, Mini • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • SCD-1020: 3.6mm fixed lens; • SCD-1040: 8mm fixed lens; • SCD-1080: 3.6x varifocal lens (2.8 ~ 10mm) • Coaxial : Pelco-C (Coaxitron)
NEW SCD-2010F  600TV Lines • 600TVL (Color) • Min. 0.04Lux @ F1.2 (Color) • 3mm fixed lens • Coax : Pelco-C (Coaxitron)	SCD-2080R/2020R  600TV Lines, IR • 600TVL (Color), 700TVL (B/W) • IR distance: SCD-2080R: 20m (66ft) • SCD-2020R: 7m (23ft) • SCD-2080R: 3.6x (2.8 ~ 10mm) varifocal lens; • SCD-2020R: 3.6mm fixed lens; • Motion Detection • Coaxial : Pelco-C (Coaxitron)	NEW SCD-2021R  650TV Lines, Compact IR • 650TVL (Color) • IR distance 20m (66ft) • 3.6mm fixed lens • Coaxial control	NEW SCD-2042R/2022R  700TV Lines IR • 700TVL (Color) • IR distance 7m (23ft) • SCD-2022R: 3.8mm fixed lens; • SCD-2042R: 8mm fixed lens • Motion Detection • Coaxial control	SCD-1020R  520TV Lines, Compact IR • 520TVL (Color) • IR distance 10m (33ft) • 3.6mm fixed lens • Coaxial control
SCV-3082  IP66 IK10 650TV Lines, Vandal • 650TVL (Color), 700TVL lines (B/W) • 0.1Lux@F1.2 (Color), 0.01Lux (B/W) • 3.9x (2.8 ~ 11mm) varifocal lens • Wide Dynamic Range • Analytics • Coax : Pelco-C (Coaxitron) • IK10, IP66	SCV-3120  IP66 IK10 600TV Lines, 12x Zoom, Vandal • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485 • IK10, IP66	SCV-2120  IP66 IK10 600TV Lines, 12x Zoom, Vandal • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.67 (Color), 0.02Lux (B/W) • Motion detection • IK10, IP66 • Pelco-C (Coaxitron), RS-485	SCV-3081/2081  IP66 IK10 600TV Lines, Vandal • 600TVL (Color), 700TVL (B/W) • SCV-3081: Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W); SCV-2081: 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.9x/3.6x (2.8 ~ 11mm/2.8 ~ 10mm) varifocal lens • Wide Dynamic Range (SCV-3081) • Analytics (SCV-3081), Motion (SCV-2081) • Coaxial : Peco-C (Coaxitron), IK10, IP66	SCV-3080/2080  IP66 IK10 600TV Lines, Vandal • 600TVL (Color), 700TVL (B/W) • SCV-3080: Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W); SCV-2080: 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.9x/3.6x (2.8 ~ 11mm/2.8 ~ 10mm) varifocal lens • Wide Dynamic Range (SCV-3080) • Analytics (SCV-3080), Motion (SCV-2080) • Coaxial : Peco-C (Coaxitron), IK10, IP66
SCV-2060  IP66 IK10 600TV Lines, Vandal • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 2.3x (2.6 ~ 6mm) varifocal lens • Motion detection • Coaxial : Pelco-C (Coaxitron) • IK10, IP66	SCV-2082R  IP66 IK10 700TV Lines, Vandal IR • 700TVL (Color) • IR distance 20m (66ft) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion Detection • Coaxial : Pelco-C (Coaxitron) • IK10, IP66	SCV-2081R/2080R  IP66 IK10 600TV Lines, Vandal IR • 600TVL (Color), 700TVL (B/W) • IR distance: SCV-2081R 20m (66ft); SCV-2080R: 30m (98ft) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion detection • Coaxial : Pelco-C (Coaxitron) • IK10, IP66	SCP-3430H/2430H  IP66 IK10 600TV Lines, 43x PTZ • 600TVL (Color), 700TVLs (B/W) • SCP-3430H: Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W); SCP-2430H: 0.2Lux@F1.65 (Color), 0.02Lux (B/W) • Wide Dynamic Range • Analytics (SCP-3430H), Motion detection (SCP-2430H) • Pelco-C (Coaxitron), RS-485/422 • IP66, IK10	SCP-3371H/3371  IP66 600TV Lines, 37x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.6 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485/422 • IP66 : SCP-3371H
SCP-3370TH  IP66 IK10 600TV Lines, 37x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.6 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics, Auto-tracking • Pelco-C (Coaxitron), RS-485/422 • IK10, IP66	SCP-2371H/2371  IP66 600TV Lines, 37x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.6 (Color), 0.02Lux (B/W) • Motion Detection • Pelco-C (Coaxitron), RS-485/422 • IP66 : SCP-2371H	SCP-2370TH  IP66 IK10 600TV Lines, 37x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.6 (Color), 0.02Lux (B/W) • Motion Detection, Auto-tracking • Pelco-C (Coaxitron), RS-485/422 • IK10, IP66	SCP-2271H/2271  IP66 600TV Lines, 27x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.6 (Color), 0.02Lux (B/W) • Motion Detection • Pelco-C (Coaxitron), RS-485/422 • IP66 : SCP-2271H	SCP-2250H/2250  IP66 IK10 600TV Lines, 25x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.65 (Color), 0.02Lux (B/W) • Analytics • RS-485/422 • IK10, IP66 : SCP-2250H

ANALOG/DVR

SAMSUNG

SAMSUNG TECHWIN

SCP-3120/3120VH  IP66 IK10 600TV Lines, 12x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics • RS-485 • IK10, IP66 : SCP-3120VH	SCP-2120  600TV Lines, 12x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.67 (Color), 0.004Lux (B/W) • Motion detection • Pelco-C (Coaxitron), RS-485	SCP-2370RH  Security Products 2013 BEST PRODUCT OF THE YEAR 600TV Lines, 37x IR PTZ • 600TVL (Color), 700TVL (B/W) • IR Distance 100m (328ft) • Motion Detection, • Pelco-C (Coaxitron), RS-485/422 • IK10, IP66 • Smart IR	SCU-9080  IP66 Weatherproof Thermal PTZ • Outstanding detection w/o lighting 1.2Km (3,937 ft) • 50mm fixed lens, 0.47mrad, Color pattern • Min. temperature of 0.08°C (32.01°F) • Event Alarm • IP66 • Pelco-C (Coaxitron), RS-485	SCU-2370  IP66 600 TV Lines, 37x PTZ • 600TVL (Color), 700TVL (B/W) • Min. 0.2Lux @ F1.6 (Color), 0.02Lux (B/W) • 37x (3.5 ~ 129.5mm) • Motion Detection • IP66 • Pelco-C (Coaxitron), RS-485
NEW SCB-6001  HD CCTV • 1080p resolution @ 30fps, 720p resolution @ 60fps • Min. 1Lux @ F1.2 (Color), 0.1Lux (B/W) • Simple Focus • Analytics • RS-485	SCB-6000  HD CCTV • 1080p resolution 30fps, 720p resolution 60fps • Min. 1Lux @ F1.2 (Color), 0.1Lux (B/W) • Motion Detection • RS-485	NEW SCO-6081R  IP66 HD CCTV Weatherproof IR • 1080p resolution 30fps, 720p resolution 60fps • IR distance 30m (90ft) • 2.8x (3 ~ 8.5mm) varifocal lens • Analytics • RS-485 • IP66	SCD-6080  HD CCTV • 1080p resolution 30fps, 720p resolution 60fps • Min. 1Lux @ F1.2 (Color), 0.1Lux (B/W) • 2.8x (3 ~ 8.5mm) varifocal lens • Motion Detection • RS-485	NEW SCD-6081R  HD CCTV • 1080p resolution 30fps, 720p resolution 60fps • IR distance 15m (49ft) • 2.8x (3 ~ 8.5mm) varifocal lens • Analytics • RS-485
SCV-6081R  IP66 HD CCTV Vandal • 1080p resolution @ 30fps, 720p resolution @ 60fps • IR distance 15m (49ft) • 2.8x (3 ~ 8.5mm) varifocal lens • Video analytics • RS-485 • IP66	SUB-2000  600 TV Lines • 600TV lines (Color) • Min. 0.05Lux @ F1.2 (Color) • Motion Detection • UTP T/X • Coax : Pelco-C (Coaxitron), RS-485	SUD-3080  600TV Lines, UTP • 600TVL (Color), 700TVL (B/W) • Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W) • 3.9x (2.8 ~ 11mm) varifocal lens • Wide Dynamic Range • Analytics • Built-in UTP TX, • Coax : Pelco-C (Coaxitron), RS-485	SUD-2081  600TV Lines, UTP • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion Detection • Built-in UTP TX • RS-485	SUD-2080  600TV Lines, UTP • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.6x (2.8 ~ 10mm) varifocal lens • Motion Detection • UTP TX • RS-485
SCB-9060  IP66 Weatherproof Thermal • Outstanding detection w/o lighting 360m (1,181 ft) • 14mm fixed lens, 1.68mrad, Color pattern • Min. temperature of 0.08°C (32.01°F) • Event Alarm • Pelco-C (Coaxitron), RS-485 • IP66	SCB-9080  IP66 Weatherproof Thermal • Outstanding detection w/o lighting 1.2Km (3,937 ft) • 50mm fixed lens, 0.47mrad Color pattern • Min. temperature of 0.08°C (32.01°F) • Event Alarm • RS-485 • IP66	DVR		
		SRD-1673D  16 Channel, 960H/D1 • 16CH 960H/D1 real-time DVR • Up to 480fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • 16CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	SRD-1670D/1670DC  16 Channel, 4CIF • 16CH 4CIF real-time DVR • Up to 480fps recording rate • Max. 5 internal HDDs • PTZ control via coaxial cable • 16CH audio inputs / 1CH audio output • DVD-RW • Smart phone support • Coaxial support: (Pelco-C (Coaxitron))	SRD-1653D  16 Channel, CIF • 16CH CIF real-time DVR • Up to 480fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • 16CH audio inputs / 1CH audio output • DVD-RW • Smart phone support
NEW SRD-1654D  16 Channel, CIF • 16CH CIF real-time DVR • Up to 480fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • 4CH audio inputs / 1CH audio output • DVD-RW • Smart phone support • Full HD 1080p video out via HDMI • Touch interface front panel	SRD-1650D/1650DC  16 Channel, CIF • 16CH CIF real-time DVR • Up to 480fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • SRD-1650DC: Pelco-C (Coaxitron) • 16CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	SRD-1652D  16 Channel, CIF • 16CH CIF real-time DVR • Up to 480fps recording rate • Max. 4 internal HDDs • 4CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	SRD-1640  16 Channel, CIF • 16CH CIF real-time DVR • Up to 480fps recording rate • Max. 1 HDD • 4CH audio inputs / 1CH audio output • USB support • Smart phone support	SRD-873D  8 Channel, 960H/D1 • 8CH D1/960H real-time DVR • Up to 240fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • 8CH audio inputs / 1CH audio output • DVD-RW • Smart phone support

877-213-1222 • www.samsung-security.com

DVR/MONITOR/LENS

SAMSUNG

SAMSUNG TECHWIN

SRD-870DC  8 Channel, 4CIF • 8CH 4CIF real-time DVR • Up to 240 fps recording rate • Max. 5 internal HDDs • PTZ control via coaxial cable • 8CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	NEW SRD-854D  8 Channel, CIF • 8CH CIF real-time DVR • Up to 240fps recording rate • Max. 4 internal HDDs • PTZ control via coaxial cable • Full HD 1080p video out via HDMI • 4CH audio inputs / 1CH audio output • DVD-RW • Smart phone support • Touch interface front panel	SRD-850D/850DC  8 Channel, CIF • 8CH CIF real-time DVR • Up to 240 fps recording rate • Max. 5 internal HDDs • SRD-850DC: PTZ control via coaxial cable • 8CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	SRD-852D/840  8 Channel, CIF • 8CH CIF real-time DVR • Up to 240 fps recording rate • SRD-852D: Max. 4 internal HDDs; • SRD-840: Max. 1 HDD • 4CH audio inputs / 1CH audio output • DVD-RW : SRD-852D • Smart phone support	NEW SRD-473D  4 Channel, 4CIF • 4CH 4CIF real-time DVR • Up to 120 fps recording rate • Max. 1 internal HDD • 4CH audio inputs / 1CH audio output • DVD-RW • Smart phone support
SRD-470D  4 Channel, 4CIF • 4CH 4CIF resolution real-time DVR • Up to 120 fps recording rate • Max. 1 internal HDD • 4CH audio inputs / 1CH audio output • DVD-RW • Smart phone support	SRD-442  4 Channel CIF, LCD • 4CH CIF real-time DVR • Up to 120fps recording rate • Max. 2 internal HDDs • 1CH audio inputs / 1CH audio output • Front panel 4.3" touch screen • Smart phone support	SRD-440  4 Channel CIF • 4CH CIF real-time DVR • Up to 120 fps recording rate • Max. 1 internal HDD • 4CH audio inputs / 1CH audio output • Smart phone support	SRD-480D  4 Channel, HD CCTV • 4CH Full HD real-time DVR • Up to 120fps recording rate • Max. 4 internal HDDs • 4CH audio inputs / 1CH audio output • Full HD 1080p video out via HDMI • DVD-R, CD-R	SVS-5R/5E  RAID 5 Unit HDD Extension Unit • 1U 19-inch rack case • Data transmission speed : Up to 3.0Gbps (SATA II) • Available SATA HDD : Up to 4TB
Encoders/Decoders		Management Software		
SPE-400/101/100  4CH / 1CH Video Encoder • Max. 30 (25)fps at 4CIF resolution • H.264, MPEG-4, MJPEG multiple codec • Multiple streaming simultaneously • 10/100/1000BASE-T : SPE-400 PoE, 10/100BASE-T : SPE-101/100 • SD memory, bi-directional audio support: SPE-400/100	SPD-400  4CH Network Video Decoder • H.264, MPEG-4, MJPEG decoding • Full HD (1080p) video output • Single and quad view • Sequence mode for multiple video sources	SSM  Central Management Software • Multi-site monitoring, Multi-client connection • Efficient alarm monitoring • Live & Map monitoring simultaneously • Multi-level group/user authority management • Device Management, Search/Playback	Smart Viewer 4.0  Easy Central Management Software • Up to 36 videos monitoring from the connected cameras • Support for full screen mode • Support for sequence function (automatic screen transition) • Favorite view & sequence of favorites • Up to 16 videos simultaneous playback simultaneously	iPOLiS mobile  Samsung network device monitoring App • View live streaming video with PTZ control • Supported format : H.264/MJPEG • Video image flip / mirror, Video image capture • Calendar search / playback / bookmark functions for DVRs / NVRs
NET-i ware  Recording Software • 16 Channel (Free) • 32 and 64 Channel (Onvif Support) • Triplex operation performance: recording, live video transmission, recorded video transmission	SPC-2000  Network Controller • Superior system compatibility • 3D joystick control • Quick and easy installation • SSM support	Monitors		
		SMT-4030/3230  40"/32" LED • Support up to 1920 x 1080 resolution • High contrast ratio 5000 : 1 • Video output : HDMI, VGA, Composite	SMT-2730  27" LED • Support up to 1920 x 1080 resolution • High contrast ratio 1000 : 1 • Video output : BNC, HDMI, VGA	SMT-2232  21.5" Wide LED • Support up to 1920 x 1080 resolution • High contrast ratio 1000 : 1 • Video output : BNC, HDMI, VGA
SMT-1930  18.5" Wide LED Monitor • Support up to 1360 x 768 resolution • High contrast ratio 1000 : 1 • Video output : HDMI, VGA, Composite	SMT-1934/1914  19" LED Monitor • Support up to 1280 x 1024 resolution • High contrast ratio 1000 : 1 • Fast response time 5ms • SMT-1934 Video output : HDMI, VGA, Composite • SMT-1914 Video output : VGA	Lenses		
		SLA-12240/880  C-mount Motorized 20x/10x Zoom • 1/2" C-mount motorized lens • 50mm lens • Auto iris : SLA-12240 (DC)/ SLA-880 (Video) • 20x optical zoom, SLA-12240 (12 ~ 240mm) • 10x optical zoom, SLA-880 (8 ~ 80mm)	SLA-3580DN/2812DN /550DV/612DN  CS-mount Auto Iris Lens • 1/3" CS-mount auto iris lens (SLA-612DN is 1/2") • F1.0/F1.4/F1.3/F1.6 DC type auto iris • Varifocal lens: SLA-3580DN (3.5 ~ 8mm); SLA-2812DN (2.8 ~ 12mm); SLA-550DV (5 ~ 50mm); SLA-612DN (6 ~ 12mm)	SLA-M2882/ M3180DN /M3180PN  CS-mount Auto Iris Megapixel • 1/3" CS-mount auto iris 1.3 MP lens (SLA-M2882) • 1/2.8" CS-mount auto iris 3 MP Lens (SLA-M3180DN) • F1.4/F1.2 DC type auto iris • Varifocal lens : SLA-M2882 (2.8~8.2mm) SLA-M3180DN/PN (3.1~8mm) • SLA-M3180PN (P-Iris)

877-213-1222 • www.samsung-security.com

ACCESSORIES

SAMSUNG

SAMSUNG TECHWIN

SHP-3701H  Outdoor Housing for PTZ Dome - For outdoor applications - Weatherproof rated to IP66 - Aluminum + Polycarbonate - IK10 vandal resistant	SHP-3701F/ SHD-3000F  In-Ceiling Housing for PTZ Dome - For indoor applications - Polycarbonate	SBP-300WM1/ 300WM  Wall Mount for PTZ Dome - Aluminum + SECC - Can be used with hanging mount and outdoor PTZ	SBP-300B  Wall Mount Install Base - Aluminum + SECC - Can be used with hanging mount and outdoor PTZ	SBP-300CM  Ceiling Mount - Aluminum + SECC - Can be used with hanging mount and Outdoor PTZ
SBP-300HM1  Hanging Mount - Aluminum - Can be used with SCP-3371/3370/3250/3120/2371/2370/2330/2271/2270/2250/2120 SNP-6201/6200/5300/5200/3371/3302/3120 SBP-300WM1/300WM/300CM/300LM	SBP-301HM2  Hanging Mount - Aluminum - Can be used with SCD-6080 SCV-3082/3081/2081R/2081 SND-7082F/7082/6084R/6084/6083/5080F/5080/3082F/3082 SNV-1080R/1080 SBP-300WM1/300WM/300CM/300LM	SBP-301HM3  Hanging Mount - Aluminum - Can be used with SCP-3371/2371/2271 SCV-3080/2120/2080R/2080/2060 SNP-6201/5300 SNV-7082/7080R/7080/6084R/6084/5084/5080R/5080/3120/3082 SBP-300WM1/300WM/300CM/300LM	SBP-300LM  Parapet Mount for PTZ Dome - Aluminum + SECC - Can be used with hanging mount and outdoor PTZ	SBP-300PM/300KM  Pole / Corner Mount - For mounts to pole - SECC - Can be used with SBP-300B/300WM/300WM1
SHB-4300H/ 4300H1/4300H2  Fixed Housing - Aluminum diecasting construction - Fully cable managed bracket - Built-in fan & heater - Support three cable glands, IP66	SHB-4200/4200H  Fixed Housing - Support two cable glands - Built-in fan & heater : SHB-4200H	STH-500/200  Fixed Housing - For fixed camera application - Wall/ceiling installations - Easy to install side open type	SBU-500WM  Fixed Mount - Wall mount for positioning system - Aluminum material - Can be used with SCU-2370/9080, SCU-VAC	SBU-220PM  Fixed Mount - Pedestal mount for positioning system - Aluminum material - Can be used with SCU-2370/9080, SCU-VAC
STB-400/4150V  Fixed Mount - Bracket for STH-500/200 : STB-400 - Bracket for box cameras : STB-4150V - Steel material	SPH-120R  HD-SDI Repeater Repeat the HD-SDI signal from the HD CCTV cameras and enables the extension for the transmission distance	SPH-110C  HD-SDI Converter Accept the HD-SDI signal from the HD CCTV cameras, and converts the signal for presentation on the HDMI input of the monitor	SPU-100TR  1 Channel UTP Transceiver - Single channel balun transceiver - No power required - Male BNC	SPU-400  4 Channel UTP Power Supply Hub - High quality video & long range transfer - Surge and lightning protection - Support RS-485 video input - Power : 300m (984ft)
SPU-400R  4 Channel UTP Receiver - High quality video & long range transfer - Surge and lightning protection - Support RS-485 video input - Video : 900m (3000ft)	SCU-EVAC  Explosion Proof Positioning System - Integrated Pan/ Tilt, and Housing 360° Pan Rotation - Tilt Range of +90° to -90° - IP66 - Telemetry Receiver : SPX-E100	 WiseNet III The WiseNetIII technology features the most advanced functions from Samsung with 1.3 megapixel and 2 megapixel cameras for high definition images. iPOLiS Your Smart Security Solution		